

WHAT IS CLAIMED IS:

1. A lateral force-measuring device for wheel, which comprises;
5 a rotator axially installed with universal function for moving in an axial direction and is dependently rotated by a rotation of a pressed wheel, and
a load-measuring device measuring a moving load for an axial direction of a rotator when a rotator is rotated.

Sub B1
10 2. The lateral force-measuring device for wheel, as claimed in claim 1, wherein said rotator axially installed with universal function for moving in an axial direction is dependently rotated by a rotation of one of a pair of pressed wheels.

15 3. A lateral force-measuring device for wheel as set forth in claim 1, which further comprises;
a dog relatively attached to said rotator with universal function for rotation, and
20 a load sensor measuring a moving load of the dog.

25 4. The lateral force-measuring device for wheel as set forth in claim 2, which further comprises;
a dog relatively attached to said rotator with universal function for rotation, and
a load sensor measuring a moving load of the dog.

5. A lateral force-measuring device for wheel as set forth in claim 1 comprises;

a wheel-driving device to rotate said wheel.

6. The lateral force-measuring device for wheel as set forth in claim 2 comprises;

a wheel-driving device to rotate said wheel.

7. The lateral force-measuring device for wheel as set forth in claim 3 comprises;

a wheel-driving device to rotate said wheel.

8. The lateral force-measuring device for wheel as set forth in claim 4 comprises;

a wheel-driving device to rotate said wheel.

9. A vehicle inspecting system incorporating a lateral force-measuring device for wheel therein as set forth in any one of claims 1 to 8.

10. A lateral force-measuring method for wheel comprises such that a wheel is pressed to a rotator axially installed with universal function for moving in an axial direction, and a rotator is dependently rotated by a rotation of a wheel to measure a moving load for an axial direction of a rotator.

Sub
B5

11. The lateral force-measuring method for wheel as set forth in claim 10, wherein one of a pair of wheels is independently pressed to a rotator axially installed with universal function
5 for moving in an axial direction.

10